



AcousticDesign™ Series AD-S.SAT

2.75-inch small format satellite
surface loudspeaker

Features

- Consistent tonal characteristics across the entire AcousticDesign Series for surface, ceiling, and pendant applications
- Refined depth and clarity even at low volume settings
- Mix-and-match capable, any subwoofer with any satellite in the AD Series SUB/SAT line
- Inverted aluminum dome dust cap
- Rated at 16 Ω
- Locking 2-pole Euroblock connectors
- Removable logo
- X-Mount™ Mini mounting hardware provides repeatable angles without drift or sag
- Intrinsic Correction™ voicings available via MP-M Series mixers and the Q-SYS Platform, including CXD-Q Series amplifiers
- Available in black (RAL 9011) or white (RAL 9010)
- Complete EASE, CF2, CAD, & BIM information available online
- UL1480 and UL2043 certified



Background Music Applications · Retail · Restaurant · Coffee Shops · Fine Dining · Hospitality · Commercial Spaces

The QSC AD-S.SAT is part of the AcousticDesign™ Series SUB/SAT loudspeaker line which are ideally suited for background music applications that require refined depth and clarity even at lower volume settings.

The AcousticDesign Series offers integrators a premium quality installed sound solution where performance, consistent coverage, and aesthetics are paramount. Specifically designed to maintain a consistent tonal characteristic across the entire family in ceiling, surface, and pendant enclosures, the AcousticDesign Series allows integrators seamless transitions within blended installations.

The AcousticDesign Series SUB/SAT loudspeakers have been specifically designed to be mix-and-match capable. Any combination of satellites may be paired with any subwoofer in the SUB/SAT line.

The AD-S.SAT features a high quality 2.75-inch weather treated paper cone woofer with an inverted aluminum dust cap for extended high frequency presence within a sealed enclosure.

These loudspeakers are rated at 16 Ω , and up to four satellites may be connected to any AcousticDesign Series SUB/SAT subwoofer's high-pass filtered outputs. Satellites also may be used as stand-alone loudspeakers using an external high-pass filter.

The input is located on the rear of the loudspeaker and uses a locking 2-pole Euroblock style connectors capable of 12AWG (2 mm) wire thickness.

To retain their stylish aesthetics, the rugged ABS baffle is further protected by using UV inhibitors that prevent discoloration. The magnetic grill features a stick-on logo that can be removed blemish-free for installations where branding is not permitted.

Installers will appreciate X-Mount™ Mini hardware that ships with the satellites. This mounting solution allows for repeatable angles without drift or sag over time. The mount may be rotated on all four 90° axes for versatile wall or ceiling mounting options.

Intrinsic Correction™ voicings that optimize performance and speed the install process are easily deployed via the MP-M Series music and paging mixers as well as the Q-SYS Platforms, including CXD-Q Series amplifiers, as part of a complete QSC systems solution.

The AD-S.SAT is available in QSC standard black (RAL 9011) or white (RAL 9010) and may be painted to match any decor.

For your system integration needs, complete EASE, CF2, CAD, and BIM files will be available for download at QSC.com.

AD-S.SAT
Preliminary

AD-S.SAT Details

Specifications

| System Details | AD-S.SAT |
|---|---|
| LF transducer | N/A |
| HF transducer | 2.75 in (70 mm) weather treated paper cone woofer |
| Effective frequency range | 150 Hz – 20 kHz |
| Rated noise power / voltage | 25 W / 20 V (rms) |
| Sensitivity [dB] (rated @1 W, 1 m) | 82 |
| Coverage (-6 dB) [°] | 170° Conical |
| Directivity factor | TBD |
| Directivity index [dB] | TBD |
| Maximum SPL [dB] (rated, 1 m (continuous / peak)) | 90 / 96 |
| Recommended amplifier | 25 W (with 1st order high-pass filter at 200 Hz) |
| Transformer taps / impedance | Bypass: 16 Ω |
| Connector | 2-pole Euroblock |
| Enclosure material | ABS |
| Grill material | Powder coated steel |
| Ingress protection | IP-34 |
| Operating environment | Designed for indoor use |
| Operating temperature range | -4 to 122° F (-20 to 50° C) |
| Net weight | 0.95 lb (433 g) |
| Product dimensions including wall bracket (H x W x D) | 3.6 x 3.5 x 5.4 in (92.5 x 89 x 136 mm) |
| Shipping weight | TBD (pair packed) |
| Shipping dimensions (H x W x D) | TBD (pair packed) |
| Included accessories | X-Mount Mini , Euroblock connector (pair packed) |
| Safety agency | Transformer UL registered per UL1876, ROHS, CE compliant. |

As part of QSC's ongoing commitment to product development, specifications are subject to change without notice.



1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174
© 2018 QSC, LLC all rights reserved. QSC and the QSC logo are registered trademarks of QSC, LLC in the U.S. Patent and Trademark office and other countries. All other trademarks are the property of their respective owners. Patents may apply or be pending.

AD-S.SAT Spec Sheet 07/17/2018



please recycle