

# whirlwind

## Medusa® Standard Specifications

### Cable

Whirlwind multipair cable, heavy duty, flexible, NEC CM rated multipair cable. Each pair contains two twisted 24GA, 7X32 polyethylene insulated conductors with 100% foil shield and 24GA drain wire. Jacket is blue PVC.

### Stage Box

Steel, 14GA base, 16GA top w/ handle  
powder coat

Kellems® strain relief/grip

Connectors - Stagebox Inputs:

Whirlwind WC3F female XLRs

Connectors - Stagebox Returns:

Whirlwind WC3M male XLRs

or

Whirlwind WCQF female 1/4" TRS jacks

### Fanout

Cable hanger (except for MINI-6 and MINI-12)

Clear tubing provided for each group of 8 channels - slides down over fan  
to help keep lines tangle-free

Heavy duty shrink tubing applied to each channel, double shrunk at  
connectors

Fanout Lengths:

Up to 8 channels - 2 ft.

9-28 channels - 3 ft.

29+ channels - 4.5 ft.

Connectors - Fanout Inputs:

Whirlwind WI3M# male XLRs, laser engraved with numbers

Connectors - Fanout Returns:

Whirlwind WI3F# male XLRs

or

Neutrik NP3C 1/4" TRS plugs

### Options

Snakeskin® cable sheathing on fanout

PigBag canvas fanout storage and protector bag

Integrated or separate storage reel

Secondary parallel split output

Other configurations and options are available on a custom build basis.